


ECO EMS22N

MANUAL PUMP ADJUSTABLE FORK

FEATURES: Adjustable Forks/Straddle Legs • Heavy Duty Steel Construction • High-Quality Powder Coat Paint Finish • Hand or Foot Pump Operation • Mechanical Parking Brake • Lightweight/Compact

2,200  CAPACITY

Lift Height: 63"/98"/118" • Raised Mast Height: 78.15"/120"/139.76" • Lowered Mast Height: 78.15"/72.25"/82"
 *Mast Height Lift @ 50"/60": 96"/100.78" • Weight (lbs): 705/795/850 • Lowered Hgt: 2.75" • Fork Dimensions: 4" x 36" • Forks Adjust (O.D.): 8.5"-33.5"
 Overall Length: 56" • Straddle Legs Adjust (I.D./O.D.): 36"-48"/43"-54" • Straddle Leg Height: 5.51" • Steer Caster: 7" x 2" • Load Rollers: 5" x 2.7"
 *For models EMS22N-98 & EMS22N-118 only

2,200 **lbs** CAPACITY  63" / 98" / 118" LIFT

EMS22N MANUAL PUMP ADJUSTABLE FORK STACKER

Model		EMS22N-63	EMS22N-98	EMS22N-118
Capacity	lbs		2200	
Load Center	(C) in		19.68	
Weight	lbs	705	795	850
Steer Casters (Polyurethane)	in		7 dia. x 2	
Load Rollers (Polyurethane)	in		5 dia. x 2	
Lowered Mast Height	(h1) in	78.15	72.25	82
Raised Mast Height	in	78.15	120	139.76
Raised Mast Height (@ 50°/60°)	in	--	96	100.78
Lowered Fork Height	(h13) in		2.75	
Raised Fork Height	(h3) in	63	98	118
Fork Dimensions	in		4 x 36	
Distance Between Forks	(b5) in		8.5 x 33.5	
Straddle Legs (I.D.)	(b2) in		36-48	
Straddle Legs (O.D.)	(b1) in		43-54	
Straddle Leg Height	in		5.51	
Handle Height (in drive position min / max)	(h14) in		29.52 / 46.06	
Overall Length	in		56	
Turning Radius	(Wa) in		50.78	

*Because of continual product improvements, specifications may be subject to change without notice

