



Collapsed View



Dual Handles



Non-Slip Solid Rubber Casters

ASGN-00

ALUMINUM SAFETY GATE

FEATURES: Large Non-Slip Rubber Tires (ideal for travel over ice/snow/uneven surfaces) • Heavy Duty Latch Bar (withstands high usage environments/will not bend or break) • Pantograph Slats and heavier overall weight allow for reduced air friction and decreased blow over accidents • Dual Handle Design eliminates pinch points • Compact Accordion Design makes storage easier • Easy set up and take down • State-of-the-Art German Casters with both Rolling/Swivel Lock ensures gate will not roll away even if on a slope or in windy conditions

240" EXTENDED LENGTH

Collapsed Length: 23.3" • Overall Width: 20" • Overall Hgt: 44.5" • Aluminum Slat Thickness: 4.8mm • Steel Gauge: 11GA

ASGN-OD CASTERS



FEATURES

- **Bracket:** Pressed steel, with double ball bearing in the swivel head, strong central kingpin, ball protection by the special top plate and ball disc design. The special dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves.
- **Wheels:** standard solid rubber, very high operational comfort, low-noise operation, very good floor preservation.
- **Tread/Tire:** Made of standard solid rubber.
- **Wheel Center/Rim:** high-quality, impact-resistant polypropylene. Pressed-on tire.

SPECIFICATIONS

Wheel Ø	160 mm
Wheel Width	40 mm
Load Capacity	135 kg
Temperature Resistance to	-20° C
Temperature Resistance to	60° C
Tread and Tire Hardness	80° Shore A

